


Echo 360 fine-wire, UV laser stripper





A turnkey workstation from

Throughput equal to multiple mechanical & chemical stripping stations.

No handling or wire rotation needed for perfect results every time.

Nothing strips fine-wire like a UV laser. with few exceptions, and none do it better than the Optec Echo 360 with it deep UV, 248 nm or 193 nm output, air-cooled, small format EXCIMER laser.

The Echo 360 is fast, versatile and safe. Optec's intuitive Process Pro[™] software control makes it easy to operate, with minimal instruction and rapid change over to different wire gauges.

The Echo 360 serves aerospace, MEMS, automotive, consumer electronics, telecom and medical devices, including cardiac rhythm, neuro, electro-physiology and many other demanding applications.

- Strip 360° without rotating the wire
- Down to 60 AWG
- Non-contact, no damage to the core
- Residue-free & oxidation-free
- No chemicals or hazardous waste
- More than 2X faster than UV YAG lasers
- Single, multi-filar, guidewires, etc.
- Wire separation & cutting options
- All wire types including magnetic wire
- Reel-to-reel & reel-to-cut & precut lengths
- Compact, self-contained, mobile
- Color touch-screen display
- 1B+ shots without factory service

Conventional lasers such as a 355 nm YAG, have a focused, Gaussian beam that scans the insulator using the highest intensity 'point' of the beam. This makes it difficult to regulate the amount of energy needed to strip the coating without changing or damaging the metal conductor.

The Echo 360's flat-top beam ablates a large area of the coating evenly by means of aperture imaging and ECHO 360° technology. This gives total control over the stripping process when transitioning from coating to core, along with sharper edges. Users can also ablate 'windows' in ribbon cables.

The deep-UV, excimer light is absorbed more readily by most insulating materials than 266 and 355 nm YAG lasers, and just enough energy is absorbed by the conductor to yield a residue-free oxide-free surface for post-process soldering, welding, bonding or crimping.



Optec's proprietary ECHO beam delivery system (BDU) irradiates the wire uniformly from all sides, stripping a submicron layer of the insulator material away with each pulse of the laser. It's high-speed, non-contact ablation make ECHO 360 the preferred choice for fine-wires.

YOUR RETURN ON INVESTMENT

- Improve quality, yield & throughput
- Innovate and protect IP
- Bring outsourced laser stripping in-house

Proof of concept samples provided upon request.

The Echo 360 the best tool for the task:

- A flat-top, imaged beam for uniform ablation
- Deep UV wavelength, no residue
- 360° simultaneous stripping
- No scanner, no wire rotation





Polymer removal 40 µm wire

Air-cooled, small-format, excimer laser

248 nm or 193 nm wavelength

Aperture imaged, flat-top beam

Purged beam path (required for 193 nm)

Coaxial, live, color, video imaging

Continuously variable, software controlled strip length

≤ 1 mm Ø static, > 1 mm dynamic stripping

60 AWG to 32 AWG * wire diameters

Spool-to-spool, spool-to-cut or manual load fixturing

Shield gas assist and debris removal

Compact, self-contained, mobile cart

Class 1, interlocked, safety enclosure

 For larger size wires, and other configurations including fully automated production systems, and TEA CO₂ models, contact Optec.